

## 1.0 TECHNICAL DATA

<u>Model</u>	<u>1000</u>	<u>1500</u>	<u>2000</u>
Working width	1.0 m	1.5 m	2.0 m
Tractor speed	Max. 12 km/h (7,5 mph), depending on the type of tractor and the condition of the ground.	Max. 12 km/h (7,5 mph), depending on the type of tractor and the condition of the ground.	Max. 12 km/h (7,5 mph), depending on the type of tractor and the condition of the ground.
Weight	494 kg (1090 lbs)	590 kg (1300 lbs)	700 kg (1543 lbs)
Container content	0,58 m <sup>3</sup> (20.5 ft <sup>3</sup> )	0,87 m <sup>3</sup> (30.7 ft <sup>3</sup> )	1,17 m <sup>3</sup> (41.3 ft <sup>3</sup> )
Machine size ( L x W x H)	1,23 x 1,18 x 1,74 m 48,4"x 46,5"x 68,5"	1,23 x 1,68 x 1,74 m 48,4"x 66,1"x 68,5"	1,23 x 2,18 x 1,74 m 48,4"x 58,8"x 68,5"
Gritting thickness	0-20 mm Depending on the driving speed, position of the dose lid and position of the dose regulator.	0-20 mm Depending on the driving speed, position of the dose lid and position of the dose regulator.	0-20 mm Depending on the driving speed, position of the dose lid and position of the dose regulator.
Recommended tractor	60 hp	60 hp	80 hp
Minimum lifting capacity	1100 kg (2865 lbs)	1300 kg (2865 lbs)	2000 kg (4410 lbs)
Three-point connection	Cat. 1 & 2	Cat. 1 & 2	Cat. 1 & 2
Minimum loading capacity of the tractor	12 l/min	12 l/min	12 l/min
Minimum pressure	70 bar	70 bar	100 bar
Necessary connections	2 x double-acting	2 x double-acting	2 x double-acting
Standard components	<ul style="list-style-type: none"> <li>- Tipping bucket</li> <li>- Powered gritting cylinder</li> <li>- Agitator</li> <li>- Continuously adjustable dose lid</li> <li>- Adjustable legs</li> </ul>	<ul style="list-style-type: none"> <li>- Tipping bucket</li> <li>- Powered gritting cylinder</li> <li>- Agitator</li> <li>- Continuously adjustable dose lid</li> <li>- Adjustable legs</li> </ul>	<ul style="list-style-type: none"> <li>- Tipping bucket</li> <li>- Powered gritting cylinder</li> <li>- Agitator</li> <li>- Continuously adjustable dose lid</li> <li>- Adjustable legs</li> </ul>