

## Parkway 3 Meteor



- [Print Specifications](#)

Dimensions: [US](#) | [METRIC](#)

### Power

<b>Engine</b>	Kubota V1505T, Vertical, water-cooled, 4-cycle diesel engine
<b>Displacement</b>	1498 cc
<b>Starting System</b>	12 V electric start
<b>Power</b>	31,3 kW a 2850 rpm
<b>Fuel Capacity</b>	51 liters

### Drive Train

<b>Traction Drive</b>	On-demand cross-flow 4 wheel drive system, 2 wheel drive in transport mode. Direct coupled variable displacement pump.
<b>Cutting Unit Drive</b>	Fixed displacement hydraulic motors

### Speed (Maximum)

<b>Cutting</b>	Forward: 12 km/h Reverse: 12 km/h
<b>Transport</b>	Forward: 25 km/h Reverse: 5 km/h

---

## Cutting Units - Meteor

<b>Type</b>	Three hydraulically driven 762mm W.O.C. Cylinders
<b>Weight Transfer</b>	Balance with hydraulic weight transfer
<b>Cutting Unit Lift</b>	Individual hydraulic lift/lower
<b>Cutting Unit</b>	Meteor, 254mm diameter, fixed head
<b>Width of Cut</b>	2.15m
<b>Height of Cut</b>	Meteor 25mm - 87mm
<b>Cutting Productivity</b>	2.5 hectares/h at 12km/h
<b>Rollers</b>	Rear full width 76mm diameter solid roll
<b>Meteor Adjustment</b>	19mm or ¾ in. tool

---

## Cutting Units - Magna

<b>Type</b>	Three hydraulically driven 762mm W.O.C. Cylinders
<b>Weight Transfer</b>	Balance with hydraulic weight transfer
<b>Cutting Unit Lift</b>	Individual hydraulic lift/lower
<b>Cutting Cylinder</b>	Magna 250 6-knife, 254mm diameter, fixed head
<b>Width of Cut</b>	2.15m
<b>Height of Cut</b>	Magna 250 13mm - 61mm
<b>Cutting Productivity</b>	2.5 hectares/h at 12km/h
<b>Rollers</b>	Rear full width 76mm diameter solid roll
<b>Magna Adjustment</b>	19mm or ¾ in. tool

---

## Brakes

<b>Service</b>	Positive hydrostatic braking
<b>Parking</b>	Fail safe, zero maintenance, oil immersed wet disc brakes

---

## Tyres

<b>Front</b>	26 x 12-12 6pr
<b>Rear</b>	20 x 10-08 4pr

---

## Steering

Hydrostatic powered steering to rear wheels

---

## Traction and Drive

**Hydraulic Tank Capacity** 42 litres

**Grade of Hydraulic Oil** ISO 46 Oil

---

## Controls

Starter key switch, throttle control lever, parking brake, cutting unit switch, individual cutting unit lift/lower control, weight transfer switch, traction pedal, steering tilt control, horn, auto diff lock, hazard warning switch, lighting kit switches (where fitted), optional rotating beacon, TST™ (Tilt Safety Technology) option

---

## Dimensions

<b>Length</b>	2.82 m
<b>Transport Width</b>	1.55 m
<b>Height with ROPS down</b>	1.5 m
<b>Weight</b>	Including Meteor mowers, with ROPS, full tanks 1410 kg
<b>Wheel Base</b>	1.5 m
<b>Wheel Track</b>	1.1 m

---

## Operator Levels

<b>Operator Ear Noise Level</b>	86 dB(A)
<b>Hand Arm Vibration levels</b>	2.31 m/s <sup>2</sup>
<b>Measured Sound Level</b>	104 dB(A)

---

## Optional Equipment

Lighting kit, rotating beacon, puncture resistant tyres, mow mode switch, storage racks, tilt stability technology (TST), 6 knife Magna 250 cylinder mower kit.

